
RTD55



RTDrill
BY REICHDRIILL

RTD55

DIMENSIONS

	Mast up	Mast down
Length	9,98 m - 32.8 ft	15,60 m - 51.2 ft
Operating width	3,05 m - 10 ft	
Height	15,21 m - 49.9 ft	4,05 m - 13.3 ft

TRANSPORT DIMENSIONS

Length	15,60 m	51.2 ft
Width	3,05 m	10 ft
Height	4,05 m	13.3 ft
Total weight	36 287 kg	80 000 lbs

UNDERCARRIAGE

Model	Reichdrill or equivalent	
Type	325 L	
Overall length	3,60 m	11.10 ft
Triple grouser	600 mm	23.62 in
Travel speed	1,45 - 2,41 km/h	0.9 - 1.5 mph
Gradeability	Up to 50%	

PULLDOWN PULLBACK

Mast	12,5 m	41 ft
Stroke	10,4 m	34 ft
Pull down	211,4 kN	47 517 lbf
Pull back	110,1 kN	24 740 lbf

MAIN FRAME

Leveling jacks	3	
Bore diameter	127 mm	5 in
Stroke	1 219 mm	48 in
Front pad size	610 mm	24 in
Rear pad size	457 mm	18 in

POWER PACK

	Tier III - Tier IV - Tier IVf - Tier V	
Engine type	Caterpillar C15 - Cummins QSX15	
Power	432 - 447 kW	580 - 600 hp
Speed	1 800 rpm	
Fuel tank	1 419 L	375 US gal

COMPRESSOR

Model	Reichdrill or equivalent	
Type	Single - two stages screw oil flooded	
Volume		
High pressure	25,5 - 38,5 m ³ /min	900 - 1 360 cfm
Low pressure	21,2 - 31,1 m ³ /min	750 - 1 100 cfm
Pressure		
High pressure	24,1 - 25,9 bar	350 - 375 PSI
Low pressure	8,6 bar	125 PSI

DRILL PIPE

Recommended hole size	127 - 172 mm	5 - 6 ¾ in
Recommended drill pipe length	9,14 m	30 ft
4+1 carousel	Ø102 - 140 mm	4 - 5 ½ in
Max drilling depth	45,57 m	149.6 ft
Single pass depth	9 m	29.6 ft

ROTARY HEAD

Type	Dual motor system	
Speed	0 - 141 rpm	
Torque	7 292 Nm	64 543 lbf-in

COOLING SYSTEM

Model	Multicore cooler package with thermostatically controlled fan	
Standard ambient	up to +54,4°C	up to 130°F

RTD55

OPERATOR CABIN

Rating: **FOPS** Standard

Noise: **Less than 82 dBA**

OPERATOR CONTROLS AND RELATED

REGEN for increased speed

Mast lock and leveling jack indicator lights

Isolated and pressurized operator's cab with A/C

Tinted safety glass

Operator vision assist system including 7 in - 178 mm LCD/LED

Two compact color cameras with 115° horizontal 86° vertical viewing angle

STANDARD EQUIPMENTS

Emergency stop shutdown located on both sides of the cab

Electronic resonating horn

Amber beacons on mast and crown

Ø 4 in (101 mm) spindle sub with 4 in API IF pin thread

Standard halogen & xenon lighting, 9 halogens and 2 xenon night lights illuminating the mast, mast table and drill deck

Safety kit including 2 hard hats and 1 fire extinguisher

24-VDC to 12-VDC power converter

AM/FM stereo radio/MP3 and two HD speakers

Drill pipe thread greasing system

OPTIONS

Angle drilling (0° - 30° in 5° increments)

Double stand-up operator's cab, includes walkway along full right side of drill base

Full walkway around perimeter of machine

Mesabi multicore cooler

6+1 pod carousel for 30 ft (9,1 m) drill pipe, Ø 4 ½ - 5 ½ in (114 - 140 mm)

9 GPM - 34,1 LPM water injection pump

NVE Dust Control, 3 600 CFM

Central service center for fuel, engine, compressor, hydraulics and coolant

Artic package

Additional standard and optional equipments are available, contact the local sales representative for pricing and availability.

Product specifications and dimensions may change without prior notice.

Our distributors



Get more details about our distributors
on <https://rtdrill.com/distributors/> or scan :



Our office

99, Troy Hawk Run Highway
Philipsburg
Pennsylvania, 16866
United States of America

+1 (814) 342-5500

contact@rtdrill.com



RTDrill
BY REICHRILL