



DIMENSIONS

	Mast up	Mast down
Length	36.6 ft 10,98 m	39 ft 11,89 m
Width	26.9 ft 8,2 m	8.2 ft 2,5 m
Height	40.9 ft 12,46 m	12.5 ft 3,81 m
Max weight	65,000 lbs 29 484 kg	

COMPRESSOR

Model	Reichdrill or equivalent	
Type	Two stages, oil flooded screw	
Delivery volume	1,070 CFM	30,3 m ³ /min
Delivery pressure	375 PSI	25,9 bar

Auxiliary blowdown valve for venting drillstring during pipe changes

Air line lubricator with 8 gal (30,3L) reservoir

ENGINE

Model	Caterpillar C13B
Power	577 HP 430 kW
Speed	1,800 rpm

PULLDOWN PULLBACK

Pullback		43,980 lbf	195,6 kN
Pullback speed	Standard	38.39 fpm	11,70 m/min
	Rapid	122.84 fpm	37,44 m/min
Pulldown		35,000 lbf	155,7 kN
Pulldown speed	Standard	24.57 fpm	7,49 m/min
	Rapid	78.62 fpm	23,96 m/min
	Regen	128.94 fpm	39,3 m/min

DRILL MAST AND RELATED

Max. table opening	22 in	559 mm
Mast stroke	28 ft	8,5 m

DRILL PIPE

Recommended hole \varnothing	up to 20 in	up to 508 mm
Recommended drill pipe length	20 ft	6,1 m
Total length capacity - 9 pod	180 ft	54,9 m
Drill pipe diameter	4 - 4.5 in	101,6 - 114,3 mm
Power breakout	Cable breakout wrench, petol® chain standard equipment	

MAIN FRAME

Leveling jacks	2 front - 2 rear		
Bore diameter	5 in	127 mm	
Stroke	Front	48 in	1 219 mm
	Rear	36 in	916 mm
Jack pad diameter	18 in	457 mm	

TRUCK

Model	Mack Granite 64 FR		
Power	505 HP		
Front axle rating	23,000 lbs		
Rear axle rating	46,000 lbs		
Lift axle (optionnal)	20,000 steerable		

OPTIONS

Rotary head: 0-141 rpm | 319 lbf | 7 292 Nm torque

Piston and centrifugal mud pump installation options

Sloped 18 pieces rod box with grab rail and pipe riser

High pressure filtration for rotation pump only

Single and dual deck mounted hammer holders

Night lighting upgrade

LED

Hydraulic driven welder installations: both with and without welder

Heavy pullback: 58 414 lbf - 259,84 kN

Extra heavy pullback: 83 154 lbf - 369 kN

ROTARY HEAD

Type	Top head hydraulic drive	
Speed	0 - 106 rpm	
Torque	7,155 lbf	9 700 Nm

Wireless radio helper's remote controls for jib swing, extend and retract

Carrousel index and lock

Winch up and 2 speed down controls

Air operated drill pipe holding wrench with hydraulic rasing-lowering

Winch: 8,500 lb (37,8 kN) with hydraulically extendable boom and 270° swing

Rod box: sloped, 15 pieces with grab rail and pipe riser

Drill pipe handling tool included as standard equipment

COOLING SYSTEM

Max. ambient	120°F	48,9°C
--------------	-------	--------

Multi-core cooler with thermostatically controlled fan speed

CONTROL STATION

Operator controle: pilot operated/lever

Platforms: operator and helper included

Folding, split helper's walkway

Lockable aluminium vandal cover

Air pressure regulator for air powered tools

20 gpm (76 l/min) direct drive water injection pump

Torque limiter control

Holdback and feed-override all with electrical on/off control

Night light: 5 halogens

Carrousel mounted stabilizer holder

Hanger arm mounted stabilizer holder

Air or hydraulic casing hammer mounting kit (hammer not included)

Casing hammer «Tubing only» kit

Steerable kit axle package

Reversing camera

Helper side storage box

Hydraulic driven welder

Engine pre-heater

Mount - Western Star

*Additional standard and optional equipments are available, contact the local sales representative for pricing and availability.
Product specifications may change without prior notice*