

---

# RTD75 SP



**RTDrill**  
BY REICHDRILL

---

# RTD75 SP

## DIMENSIONS

	Mast up	Mast down
Length	14,2 m - 46.5 ft	23,9 m - 78.6 ft
Operating width	6,8 m - 22.5 ft	
Height	23,8 m - 78 ft	5,5 m - 18.7 ft

## SHIPPING DIMENSIONS

### BASE

Length	14 m	46 ft
Width	4,27 m	14 ft
Height	4,27 m	14 ft

### MAST

Length	21,6 m	71 ft
Width	2,1 m	6.8 ft
Height	1,89 m	6.2 ft
Total weight	85 275 kg	188 000 lbs

6,1 m - 20 ft **Shipping container:** partial cab, support, walkways, misc parts

Estimated weight: 6 803 kg - 15 000 lbs

## UNDERCARRIAGE

Model	Reichdrill or equivalent	
Type	D8	
Overall length	5,99 m	19 ft 8 in
Triple grouser	800 m	31.5 in
Travel speed	1,29 - 2,1 km/h	0.8 - 1.3 mph
Gradeability	Up to 45%	

## PULLDOWN PULLBACK

Mast	22 m	72 ft
Stroke	18,9 m	62 ft
Pulldown	421 kN	94 700 lbf
Pullback	125 kN	28 075 lbf

## MAIN FRAME

Leveling jacks	One front and two rear	
Bore diameter	203 mm	8 in
Stroke	1 219 mm	48 in
Pad size - front	965 mm	38 in
Pad size - rear	660 mm	26 in

## POWER PACK

	Tier III - IV final	
Engine type	Caterpillar C27 - Cummins QSK23	
Power	708 kW	950 hp
Speed	1 800 rpm	
Fuel tank	3 028 L	800 US gal

## COMPRESSOR

Model	Reichdrill or equivalent	
Type	Single - two stages screw oil flooded	
Volume		
Min	42,5 m <sup>3</sup> /min	1 500 CFM
Max	76,5 m <sup>3</sup> /min	2 700 CFM
Pressure		
Min	6,9 bar	100 PSI
Max	25,9 bar	375 PSI

## DRILL PIPE

Recommended hole size	229 - 311 mm	9 - 12 ¼ in
Recommended drill pipe length	7,62 m	25 ft
4+1 carousel	Ø 178 - 219 mm	Ø 7 - 8 ⅝ in
Max drilling depth	40,8 m	134 ft
Single pass depth	17,98 m	59 ft

## ROTARY HEAD

Type	Dual motor system	
Speed	0 - 141 rpm	
Torque	14 585 Nm	10 757 lbf-ft

## COOLING SYSTEM

Model	Multicore cooler package with thermostatically controlled fan	
Standard ambient	up to 54,4°C	up to 130°F

---

# RTD75 SP

## OPERATOR CABIN

Rating: 2 persons operator's **FOPS** cab

Noise: **Less than 75 dBA**

Controls: **Electric - hydraulic**

## OPERATOR CONTROLS AND RELATED

REGEN for increased speed

Mast lock and leveling jack indicator lights

Isolated and pressurized operator's cab with A/C

Tinted safety glass

Operator vision assist system including 7 in - 178 mm LCD/LED

Two compact color cameras with 115° horizontal 86° vertical viewing angle

Walkway from operator's cab to right deck and access ladder

## STANDARD EQUIPMENTS

24-VDC to 12-VDC power converter

AM/FM stereo radio/MP3 and two HD speakers

Drill pipe thread greasing system

Ø 4 in (101 mm) spindle sub with 4 in API IF pin thread

Standard halogen & xenon lighting, 9 halogens and 2 xenon exterior night lights illuminating the mast, mast table and drill deck

9 gpm (34.1 LPM) water injection pump (water tank is optional)

Safety kit including 2 hard hats and 1 fire extinguisher

## OPTIONS

Centralized lubrication

Full walkways: from cab to right side, left side, rear of cab and mast work deck

Auxiliary 600 GAL - 2 271 L water tank

Cold weather package

NVE Dust Control, 7 200 CFM - 204 m<sup>3</sup>/min capacity

Fire suppression systems

Upgraded lighting package LED

Compressor variable volume control

Central service center for fuel, engine, compressor, hydraulic and coolant fluids

*Additional standard and optional equipments are available, contact the local sales representative for pricing and availability.*

*Product specifications and dimensions may change without prior notice.*

---

---

# Our distributors



Get more details about our distributors  
on <https://rtdrill.com/distributors/> or scan :



## Our office

99, Troy Hawk Run Highway  
Philipsburg  
Pennsylvania, 16866  
United States of America

+1 (814) 342-5500

contact@rtdrill.com



**RTDrill**  
BY REICHRILL