
RTD75



RTDrill
BY REICHDRILL

RTD75

DIMENSIONS

	Mast up	Mast down
Length	18,6 m - 61.11 ft	14,1 m - 46 ft
Operating width	6,8 m - 22.5 ft	
Height	18,1 m - 59.1 ft	5,5 m - 18.7 ft

SHIPPING DIMENSIONS

BASE

Length	13,96 m	45.8 ft
Width	4,27 m	14 ft
Height	3,99 m	13.10 ft

MAST

Length	16,06 m	52.7 ft
Width	1,89 m	6.2 ft
Height	1,89 m	6.2 ft
Total weight	81 647 kg	180 000 lbs

6,1 m - 20 ft **Shipping container:** partial cab, support, walkways, misc parts

Estimated weight: 6 803 kg - 15 000 lbs

UNDERCARRIAGE

Model	Reichdrill or equivalent	
Type	D8	
Overall length	5,99 m	19 ft 8 in
Triple grouser	800 m	31.5 in
Travel speed	1,29 - 2,1 km/h	0.8 - 1.3 mph
Gradeability	Up to 45%	

PULLDOWN PULLBACK

Mast	15,2 m	50 ft
Stroke	13,4 m	44 ft
Pull down	404,2 kN	98 960 lbf
Pull back	244,6 kN	54 978 lbf

MAIN FRAME

Leveling jacks	One front and two rear	
Bore diameter	203 mm	8 in
Stroke	1 219 mm	48 in
Pad size - front	965 mm	38 in
Pad size - rear	660 mm	26 in

POWER PACK

Tier III - IV final

Engine type	Caterpillar C27 - Cummins QSK23	
Power	708 kW	950 hp
Speed	1 800 tr/min	
Fuel tank	3 028 L	800 US gal

COMPRESSOR

Model	Reichdrill or equivalent	
Type	Single - two stages screw oil flooded	
Volume		
Min	31,8 m ³ /min	1 370 cfm
Max	76,5 m ³ /min	2 700 cfm
Pressure		
Min	8,6 bar	125 psi
Max	25,9 bar	375 psi

DRILL PIPE

Recommended hole size	229 - 311 mm	9 - 12 ¼ in
Recommended drill pipe length	9,14 m	40 ft
4+1 carousel	Ø 178 - 219 mm	Ø 7 - 8 ⅝ in
Max drilling depth	61 m	200 ft
Single pass depth	12,04 m	39.6 ft

ROTARY HEAD

Type	Dual motor system	
Speed	0 - 141 rpm	
Torque	16 107 Nm	142 560 lbf-in

COOLING SYSTEM

Model	Multicore cooler package with thermostatically controlled fan	
Standard ambient	up to 54,4°C	up to 130°F

RTD75

OPERATOR CABIN

Rating: 2 persons operator's **FOPS** cab **ISO3449**

Noise: **Less than 75 dBA**

Controls: **Electric - hydraulic**

OPERATOR CONTROLS AND RELATED

REGEN for increased speed

Mast lock and leveling jack indicator lights

Isolated and pressurized operator's cab with A/C

Tinted safety glass

Operator vision assist system including 7 in - 178 mm LCD/LED

Two compact color cameras with 115° horizontal 86° vertical viewing angle

Walkway from operator's cab to right deck and access ladder

STANDARD EQUIPMENTS

24-VDC to 12-VDC power converter

AM/FM stereo radio/MP3 and two HD speakers

Drill pipe thread greasing system

Ø 4 in (101 mm) spindle sub with 4 in API IF pin thread

Standard halogen & xenon lighting, 9 halogens and 2 xenon exterior night lights illuminating the mast, mast table and drill deck

9 gpm (34.1 LPM) water injection pump (water tank is optional)

Safety kit including 2 hard hats and 1 fire extinguisher

OPTIONS

Angle drilling (0° - 30° in 5° increments)

Full walkways: from cab to right side, left side, rear of cab and mast work deck

Rotary head: 0 - 106 rpm @ 190 081 lbf-in 21 476 Nm torque

Mesabi multicore cooler

Angle drilling - 0° - 20° in 5° increments or 0° - 30° in 5° increments

3+1 (max depth: 48,62 m - 159.6 ft) carousel for up to Ø 9 5/8 in (244 mm) drill pipe, up to 40 ft (12,2 m) length

5+1 (max depth: 73 m - 239.6 ft) carousel for up to Ø 8 5/8 in (219 mm) drill pipe, up to 40 ft (12,2 m) length

Auxiliary 600 GAL - 2 271 L water tank

NVE Dust Control, 7 200 CFM - 204 m³/min capacity

Cold weather package

Fire suppression systems

Upgraded lighting package LED

Additional standard and optional equipments are available, contact the local sales representative for pricing and availability.

Product specifications and dimensions may change without prior notice.

Our distributors



Get more details about our distributors
on <https://rtdrill.com/distributors/> or scan :



Our office

99, Troy Hawk Run Highway
Philipsburg
Pennsylvania, 16866
United States of America

+1 (814) 342-5500
contact@rtdrill.com



RTDrill
BY REICHRILL